

The PIC chip to support: (increasing with the software update)

10 Series:

PIC10F200 PIC10F202 PIC10F204 PIC10F206 12C Series: PIC12C508 PIC12C508A
PIC12C509 PIC12C509A PIC12C671 PIC12C672 PIC12CE518 PIC12CE519 PIC12CE673
PIC12CE674

12F Series:

PIC12F508 PIC12F509 PIC12F629 PIC12F675 PIC12F683 16C Series: PIC16C505
PIC16C554 PIC16C558 16C61 16C62 16C62A 16C62B 16C64 PIC16C64A PIC16C65
PIC16C63 PIC16C63A PIC16C66 PIC16C66A PIC16C67 PIC16C620 16C65A PIC16C65B
PIC16C620A PIC16C621 PIC16C621A PIC16C622 PIC16C622A PIC16C71 PIC16C71A
PIC16C72 PIC16C72A PIC16C74 PIC16C74A PIC16C73B 16C73 PIC16C73A PIC16C76
PIC16C77 PIC16C710 PIC16C711 PIC16C712 PIC16C74B PIC16C716 PIC16C745
PIC16C765 PIC16C773 PIC16C774 PIC16C83 PIC16C84

16F Series:

PIC16F54 PIC16F57 PIC16F627 PIC16F630 PIC16LF627A PIC16F648A PIC16F628A
PIC16F627A PIC16F628 PIC16F676 PIC16F683 PIC16LF628A PIC16F684 PIC16F688
PIC16F72 PIC16F73 PIC16F74 PIC16F76 PIC16F77 PIC16F737 PIC16F747 PIC16F767
PIC16F777 PIC16F83 PIC16F84 PIC16F84A PIC16F87 PIC16F88 PIC16F818 PIC16F819
PIC16F870 PIC16F871 PIC16F872 PIC16F873 PIC16F873A PIC16F874 PIC16F874A
PIC16F876 PIC16F876A PIC16F877 PIC16LF873A PIC16F877A

18 Series:

PIC18F242 PIC18F248 PIC18F252 PIC18F258 PIC18F442 PIC18F448 PIC18F452
PIC18F458 PIC18F1220 PIC18F1320 PIC18F2220 PIC18F2320 PIC18F4220 PIC18F4320
PIC18F6525 PIC18F6621 PIC18F8525 PIC18F8621 PIC18F2331 PIC18F2431 PIC18F4331
PIC18F4431 PIC18F2455 PIC18F2550 PIC18F4455 PIC18F4550 PIC18F4580 PIC18F2580
PIC18F2420 PIC18F2520 PIC18F2620 PIC18F6520 PIC18F6620 PIC18F6720 PIC18F6585
PIC18F6680 PIC18F8585 PIC18F8680

Plug and Play with USB communication. convenient desktop and laptop computers without serial ports use 2 programming speed much faster than the PICSTART-PLUS. 3. can easily read the contents of the chip program area. 4 automatic programming verification. 5. comprehensive information prompt to the user a clear understanding of the working state. 6 programmer with a ZIF 40pin Block, direct programming 8pin- 40pin DIP-chip 7. 8pin-40 pin-board outside the chip through the ICSP output direct download